MS7120 Orbit

Omnidirectional Laser Scanner

Honeywell's MS7120 Orbit® provides aggressive omnidirectional scanning in an award-winning design for retailers seeking an affordable, aesthetically pleasing scanning solution.

Orbit, the all-time, best-selling hands-free omnidirectional scanner, presents an innovative, elegant and affordable solution to convenience retail applications where counter space is at a premium.

Compact, lightweight and rugged, Orbit maximizes customer satisfaction and employee efficiency with a patented 20-line scan pattern, an easy-to-find sweet spot and a scan speed of 1,120 scans per second.

The scanner's expanded ability to update its firmware via Honeywell's patented MetroSet®2 configuration software (provided free) safeguards long-term infrastructure commitments in the event of a change in the POS system or software.

Recipient of multiple design honors, Orbit's award-winning shape enables hand-held scanning of large, bulky items. For added flexibility, the scanning head can be tilted within a 30° range to accommodate objects of various sizes and shapes.

Standard features include user-replaceable cables, Honeywell's patented MetroSelect and MetroSet®2 for easy configuration, data editing and OPOS/JPOS compatibility for easy installation.

For more information on the MS7120 Orbit omnidirectional laser scanner, please visit www.honeywell.com/aidc



greatpages.ca
BY ADVANCED CUSTOM SYSTEMS
Printers, labels, supplies, matched

Features

- **20 Scan Line Omnidirectional Pattern:** Provides aggressive scanning as an additional benefit to hand presentation applications
- **Sweet Spot Scanning:** Engineered "sweet spot" to optimize scan performance and first pass read rate
- **Adjustable Scan Head:** Ability to tilt scanner 30° for targeted scanning or larger products
- **Flash ROM:** Protects POS investment with free firmware updates via MetroSet®2 software and standard PC
- **Automatic Scanning Operation:** Simply present a bar code and the unit scans in a single pass

MS7120 Orbit Technical Specifications

Operational	
Light Source	Visible Laser Diode 650 nm ± 10 nm
Visual Indicators	Blue = ready to scan; White = good read
Host System Interfaces	USB, RS232, Keyboard Wedge, IBM 468xx (RS485), Light Pen Wand Emulation
Mechanical	
Dimensions (LxWxH)	105 mm x 102 mm x 150 mm (4.1˝ x 4.0˝ x 5.9˝)
Weight	400 g (14.1 oz)
Electrical	
Input Voltage	5 VDC ± 0.25 V
Operating Power (typical)	900 mW (180 mA @ 5 V)
Standby Power (typical)	850 mW (170mA @ 5 V)
DC Transformers	Class 2: 5.2 VDC @ 1 A
Laser Class	Class 1: IEC60825-1, EN60825-1
EMC	FCC Part 15, ICES-003, EN55022 Class B
Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	5% to 95% relative humidity, non-condensing
Drop	Designed to withstand 1.2 m (4´) drops
Environmental Sealing	Sealed to resist airborne particulate contaminants
Light Levels	4842 Lux (450 foot-candles)
Scan Performance	
Scan Pattern	Omnidirectional: 5 fields of 4 parallel lines
Scan Speed	1120 scan lines per second
Print Contrast	35% minimum reflectance difference
Pitch, Skew	60°, 60°
Decode Capability	Reads standard 1D and GS1 DataBar symbologies. Visit www.honeywell.com/aidc/symbologies for details.
Warranty	3 year factory warranty

Typical Performance*	
Narrow Width	Depth of Field
5.2 mil	25 mm - 50 mm (1.0˝ - 2.0˝)
7.5 mil	0 mm - 150 mm (0˝ - 5.9˝)
10 mil	0 mm - 175 mm (0˝ - 6.9˝)
13 mil	0 mm - 215 mm (0˝ - 8.5˝)
26 mil	25 mm - 250 mm (0˝ - 9.8˝)

*Resolution: 5 mil (0.125 mm)
*Performance may be impacted by bar code quality and environmental conditions

For more information:
www.honeywell.com/aidc

Honeywell Security & Data Collection
Honeywell Scanning & Mobility
90 Coles Road
Blackwood, NJ 08012
856.228.8100
www.honeywell.com

© 2009 Honeywell International Inc.